



Perbadanan Harta Intelek Malaysia
Intellectual Property Corporation of Malaysia

Aras 27, 30 dan 32, Menara Dayabumi, Jalan Sultan Hishamuddin, 50623 Kuala Lumpur, Malaysia

Tel : 603-2274 2100 Fax : 603-2274 1332 Website : www.mipc.gov.my

To:

Lim Chong Chuan

Lim Chong Chuan & Associates

3-1 Jalan 3 / 116D

Kuchai Entrepreneurs Park,

Off Jalan Kuchai Lama,

58200 Kuala Lumpur.

PATENT APPLICATION NO: PI 2002 4247

This is to certify that annexed hereto is a true copy from the records of the Registry of Trade Marks and Patents, Malaysia of the application as originally filed which is identified therein.

By Authority of the
REGISTRY OF PATENTS



ABDUL RAHMAN RAMLI
(CERTIFYING OFFICER)

27 June 2003



KEMENTERIAN PERDAGANGAN DALAM NEGERI
DAN HAL EHWAL PENGGUNA MALAYSIA
BAHAGIAN HARTA INTELEK,
TINGKAT 27 & 32,
MENARA DAYABUMI,
JALAN SULTAN HISHAMUDDIN,
50654 KUALA LUMPUR.
*Ministry of Domestic Trade and Consumer Affairs Malaysia
Intellectual Property Division.*


*Telefon : 03 - 22742100
Fax : 03 - 22741332*

CERTIFICATE OF FILING

APPLICANT : IQ GROUP SDN BHD
APPLICATION NO : PI 20024247
REQUEST RECEIVED ON : 13/11/2002
FILING DATE : 13/11/2002
AGENT'S/APPLICANT'S FILE REF. : P2002481

Please find attached, a copy of the Request Form relating to the above application, with the filing date and application number marked thereon in accordance with Regulation 25(1).

Date : 15/11/2002


(ROZILEE BIN ASID)
for Registrar of Patents

To : LIM CHONG CHUAN
C/O LIM CHONG CHUAN & ASSOCIATES,
3-1, JALAN 3/116D, KUCHAI ENTREPRENEURS' PARK,
OFF JALAN KUCHAI LAMA,
58200-KUALA LUMPUR
MALAYSIA

<p>Pat nts Form No. 1</p> <p>PATENTS ACT 1983</p> <p>REQUEST FOR GRANT OF PATENT [Regulation 7(1)]</p> <p>To: The Registrar of Patents Patent Registration Office Kuala Lumpur, Malaysia</p>	<p style="text-align: right;">For Official Use</p> <p>Application no: <u>P 20024247</u></p> <p>Filing date: <u>13-11-2002</u></p> <p>Request received on: <u>13-11-2002</u></p> <p>* Fee received on: <u>13-11-2002</u></p> <p>Amount: <u>RM 200</u></p> <p>* Cheque/Postal Order/Money Order/Draft/Cash No: <u>54465 400535</u></p>
<p>Please submit this form in duplicate together with the prescribed fee.</p>	<p>Applicant's Agent's file reference: <u>P20020481</u></p>
<p>THE APPLICANT(S) REQUEST(S) THE GRANT OF A PATENT IN RESPECT OF THE FOLLOWING PARTICULARS:</p> <p>I. TITLE OF INVENTION: <u>TOOL-FREE ADJUSTABLE LAMP FIXTURE</u></p> <p>_____</p> <p>_____</p>	
<p>II. APPLICANT(S) (the data concerning each applicant must appear in this box or, if the space is insufficient in the space below):</p> <p>Name: <u>IQ GROUP SDN. BHD.</u></p> <p>_____</p> <p>H.S.C. / Passport No: _____</p> <p>Address: <u>149 Jalan Sultan Azlan Shah</u></p> <p><u>Taman Perindustrian Bayan Lepas</u></p> <p><u>Fasa 1 (FTZ), Bayan Lepas</u></p> <p><u>11900 Penang</u></p> <p>_____</p> <p>Address for service in Malaysia: <u>LIM CHONG CHUAN & ASSOCIATES, 3-1 Jalan 3/116D,</u> <u>Kuchai Entrepreneurs' Park, Off Jalan Kuchai Lama, 58200 Kuala Lumpur.</u></p> <p>Nationality: <u>A Malaysian Company</u></p> <p>* Permanent residence principal place of business: <u>as above</u></p> <p>_____</p> <p>Telephone number: <u>03-79829887</u> Facsimile number: <u>03-79810188</u></p>	
<p>Additional Information (if any):</p>	

* Delete where inapplicable.

20024247

III. INVENTOR

Applicant is the inventor:

Yes

☐

No

☒

If the applicant is not the inventor:

Name of inventor: YEOH KEAT HOCK

Address of inventor: 149 Jalan Sultan Azlan Shah

Taman Perindustrian Bayan Lepas

Fasa 1 (FTZ), Bayan Lepas, 11900 Penang

A statement justifying the applicant's right to the patent accompanies this form:

Yes

☒

No

☐

Additional Information (if any):

IV. AGENT OR REPRESENTATIVE

Applicant has appointed a patent agent in accompanying Form No. 17:

Yes

☒

No

☐

Agent's registration number: PA/86/0009

Applicants have appointed _____ to be their common representative.

V. DIVISIONAL APPLICATION

This application is a divisional application

☐

The benefit of the filing date

☐

priority date

☐

of the initial application is claimed inasmuch as the subject matter of the present application is contained in the initial application identified below:

Initial application no: _____

Date of filing of initial application: _____

VI. DISCLOSURES TO BE DISREGARDED FOR PRIOR ART PURPOSES

Additional information is contained in supplemental box:

(a) Disclosure was due to acts of applicant or his predecessor in title

☐

Date of disclosure: _____

(b) Disclosure was due to abuse of rights of applicant or his predecessor in title

☐

Date of disclosure: _____

A statement specifying in more detail the facts concerning the disclosure accompanies this Form:

Yes

☐

No

☐

Additional Information (if any):

VII. PRIORITY CLAIM (if any)

The priority of an earlier application is claimed as follows:

Country (if the earlier application is a regional or international application, indicate the office with which it is filed):

Filing date: _____

Application no: _____

Symbol of the International Patent Classification:

If not yet allocated, please tick ☐

The priority of more than one earlier application is claimed:

Yes ☐

No ☐

The certified copy of the earlier application(s) accompanies this form:

Yes ☐

No ☐

If No, it will be furnished by _____ (date)

Additional Information (if any):

VIII. CHECK LIST

A. This application contains the following:

- | | | |
|----------------|----|----------|
| 1. request | | |
| 2. description | 6 | sheet(s) |
| 3. claim(s) | 2 | sheet(s) |
| 4. abstract | 1 | sheet(x) |
| 5. drawing(s) | 4 | sheet(s) |
| Total | 13 | sheet(s) |

B. This form, as filed, is accompanied by the items checked below:

- | | |
|---|-------------------------------------|
| (a) signed Form no. 17 | <input checked="" type="checkbox"/> |
| (b) declaration that inventor does not wish to be named in the patent | <input type="checkbox"/> |
| (c) statement justifying applicant's right to the patent | <input checked="" type="checkbox"/> |
| (d) statement that certain disclosures be disregarded | <input type="checkbox"/> |
| (e) priority document (certified copy of earlier application) | <input type="checkbox"/> |
| (f) cash , cheque, money order , bankers draft or postal order for the payment of application fee | <input checked="" type="checkbox"/> |
| (g) other documents (specify) | <input type="checkbox"/> |

2024247

IX. SIGNATURE: _____

Date: 11 November 2002

LIM CHONG CHUAN

~~(Applicant)~~ / Agent)

If agent, indicate agent's registration no: PA/86/0009

For Official Use

1. Date application received: _____

2. Date of receipt of correction, later filed papers or drawings completing the application:

* Type name under signature and delete where inapplicable.

TOOL-FREE ADJUSTABLE LAMP FIXTURE

TECHNICAL FIELD

This invention relates to a tool-free adjustable lamp fixture, which can be selectively tilted or rotated from its installed position.

5 BACKGROUND OF THE INVENTION

A conventional lamp fixture carries at least one lamp and a motion detection device. The conventional lamp fixture may be installed in various mounting positions such as on wall or on ceiling. The fixture comprises a lamp holder, an intermediate joint body and a wall plate. As seen in Figure 1, a first end of the joint body is attached to the wall plate with
10 the assistance of a lock nut. The lamp holder is attached to a side end of the joint body with the assistance of a wing nut laterally disposed. When a user wishes to adjust the position of the lamp fixture, the user needs to loosen the wing nut in order to achieve a tilting adjustment. Otherwise, the user needs to loosen the lock nut in order to achieve a rotational adjustment.

15 A tool such as a pliers and manual turning (by hand) are required to achieve the above adjustments. In the case of the lock nut, manual turning with certain amount of force may also be required. After the adjustment is made, a tool is again required to tighten the nut.

The conventional lamp fixture is installed at a mounting height of 2.5m to 3.5m. It is indeed not user-friendly as well as unsafe to a technician who has to climb up a ladder,
20 and uses both hands to carry out the adjustments.

SUMMARY OF THE INVENTION

The present invention has therefore as a primary object to improve the conventional lamp fixture, so that no hand tool is required for both rotational and tilting adjustments.

The above object is achieved in that a first set of standard screw and spring mechanism is
25 applied to an open terminal end of an intermediate connector body, and a second set of

standard screw and spring mechanism is applied to one lateral end of the intermediate connector body linking a lamp holder.

For rotational adjustment of the invention, a user simply rotates the fixture. For tilting adjustment, the user simply tilts the lamp holder to a desired position, and the lamp
5 holder will be locked into position.

Another object of this invention is to provide a tool-free adjustable lamp fixture that is relatively simple and handy to be handled.

BRIEF DESCRIPTION

In order that the present invention may be more readily understood, the following
10 description is given, by way of example, of one specific embodiment of a tool-free adjustable lamp fixture carrying two lamps and a motion detection device made in accordance with the present invention. Reference will be made to the accompanying drawings, in which:

Figure 1 shows an isometric view of one embodiment of a conventional lamp fixture
15 carrying two lamps and a motion detection device mounted on a wall.

Figure 2a shows an isometric view of one embodiment of the present invention carrying two lamps and a motion detection device.

Figure 2b shows an about-to-assemble partial view of various components making up the invention to a lamp holder.

20 Figure 3a shows a partial side view of an intermediate connector body, in communication with a lamp holder, in a locked position.

Figure 3b shows a partial side view of an intermediate connector body, in communication with a lamp holder when the lamp holder is being adjusted.

DETAILED DESCRIPTION

For ease of explanation, like numerals are used for similar components. Alphabets "a" and "b" are used to denote different sets of similar components in the invention.

Figure 2a shows one embodiment of the present invention with two lamps and one motion detection device. In Figure 2b, an about-to-assemble view of various components to one lamp holder is shown. The invention comprises substantially a mounting plate (1), at least a first set of standard screw and spring mechanism (4a, 5a, 6a), at least an intermediate connector body (2), at least a second set of standard screw and spring mechanism (4b, 5b, 6b), a motion detection device and at least a lamp holder (3). The first set of standard screw and spring mechanism (4a, 5a, 6a) is applied to one open terminal end (21) of the intermediate connector body (2) engaging the mounting plate (1), and the second set of standard screw and spring mechanism (4b, 5b, 6b) is applied to one lateral end (23) of the intermediate connector body (2) linking the lamp holder (3). The standard screw and spring mechanism comprises a shoulder screw (4), a tower spring (5) and a compression ring (6). The function of the compression rings (6a, 6b) in the two sets of screw and spring mechanisms is to provide an electrical earth-continuity from the mounting plate (1) through the intermediate connector body (2) to the lamp holder (3).

The intermediate connector body (2) is substantially cylindrical in shape. The open terminal end (21) is aligned with the central axis of the cylindrical connector body (22). The open terminal end (21) contains a receptor to receive the first shoulder screw (4a). The circumference of the open terminal end (21) of the intermediate connector body (2) is appropriately serrated as in a toothed gear (hereafter referred to as gear C). The adjacent portion of the mounting plate (1) is also appropriately serrated as in a toothed gear (hereafter referred to as gear D). The two gears C and D are meshed or mated with each other when the mounting plate (1) is engaged with the open terminal end (21). It is important to note that an O-ring (7a) is sandwiched between the open terminal end (21) of the intermediate connector body (2) and the mounting plate (1). The function of the O-ring (7a) is to provide a water seal to protect internal parts from water ingress.

Two lateral ends (23, 24) are provided on two sides of the intermediate connector body (2) on its other end. The lateral ends (23, 24) define a lateral axis which is at right angle to the central axis of the cylindrical connector body (22). A passageway traverses the two lateral ends (23, 24), so that a second shoulder screw (4b) is allowed to traverse
 5 from one lateral end (23) to the other lateral end (24) of the cylindrical connector body (22) adjoining a lamp holder (3). The circumference of one lateral end (24) of the intermediate connector body (2) is appropriately serrated as in a toothed gear (hereafter referred to as gear B). This serrated lateral end (24) will mesh or mate with a similarly serrated end (31) (hereafter referred to as gear A) on the lamp holder (3). This meshing
 10 or mating will prevent the lamp holder (3) from dislocating from its position. It is important to note that another O-ring (7b) is disposed in between the serrated lateral end (24) of the intermediate connector body (2) and the serrated end (31) of the lamp holder (3). The function of the O-ring (7b) is to provide a water seal to protect internal parts from water ingress.

15 The second set of screw and spring mechanism (4b, 5b, 6b) is installed to the un-serrated lateral end (23) of the intermediate connector body (2). A gasket (8) is disposed between the compression ring (6b) and the tower spring (5b). The function of the gasket (8) is to provide a water seal to protect internal parts from water ingress.

Referring to Figures 3a and 3b, the tilting adjustment can be explained. The second set of
 20 screw and spring mechanism (4b, 5b, 6b) is relied to facilitate a tilting adjustment. When an external force is applied to tilt the lamp holder (3), a rotational force is exerted between the lamp holder (3) and the intermediate connector body (2). The gear A at the lamp holder (3) and the gear B at the intermediate connector body (2) will move relative to each other. The second tower spring (5b) will compress and make way to allow the
 25 lamp holder (3) to tilt. When the external force is removed (i.e. the tilting action stops), the tower spring (5b) will relax and push the gear A and gear B (between the lamp holder (3) and the intermediate connector body (2)) to mate or mesh. The mating or meshing of the gear teeth or serrations (A and B) on the lamp holder (3) and the intermediate connector body (2) will prevent the lamp holder (3) from further change of position due

to its weight. It also gives a 'click' feeling during the tilting adjustment. A screw cover (9) is employed to cover the second shoulder screw (4b).

When the invention is installed in normal position, the second shoulder screw (4b) is tightened until a pre-determined torque, which will produce adequate compression force onto the second tower spring (5b) and ensures that the gear A (on the lamp holder (3)) and the gear B (on the intermediate connector body (2)) shall mate or mesh properly peak to valley. The second tower spring (5b) characteristics shall be chosen, such that this compression force is sufficient to hold the intermediate connector body (2) and the lamp holder (3) with a lamp affixed. The lamp holder (3) is prevented from moving under its own weight. At this stage, the height of the second tower spring (5b) is denoted by dimension Z.

When an external force is applied to tilt the lamp holder (3), a rotational force is exerted between the lamp holder (3) and the intermediate connector body (2). The gear A at the lamp holder (3) and the gear B at the intermediate connector body (2) will move relative to each other. The peaks of gear A will slide up from the corresponding valleys of gear B, until the peaks of both gear A and gear B touch each other. This movement causes the lamp holder (3) to move downwards, and increases the compression force on the tower spring (5b). At this stage, the height of the tower spring (5b) is reduced to dimension Z minus dimension Y, where Y being the displacement of lamp holder (3) along the longitudinal axis of the shoulder screw (4b).

With further tilting force applied between the lamp holder (3) and the intermediate connector body (2), the peaks of gear A shall slide past the peaks of gear B. The compressed tower spring (5b) shall assist the movement until the peaks of gear A mate or mesh with the next valleys of gear B. This mechanism produces the characteristic 'click' feeling. The tower spring (5b) shall relax back to original compression state. If the tilting force ceases, then the tower spring (5b) together with the gears A and B shall hold the lamp holder (3) at that position relative to the intermediate connector body (2). If the tilting force continues to be exerted, then gear A will continue to roll over gear B from valley to valley, until the user is satisfied with the final position and then cease applying the tilting force.

The description above is for tilting adjustment, but the same mechanism is also applicable to rotational adjustment. The first set of screw and spring mechanism (4a, 5a, 6a) engages the mounting plate (1) and the open terminal end (21) of the intermediate connector body (2). Essentially, the rotation of the lamp holder (3) is achieved about the
5 axis of the first shoulder screw (4a). An O-ring (7a) is similarly employed, but no gasket is needed for this engagement. This is because the mounting plate (1) is mounted with the assistance of another gasket, hence the space inside the mounting plate (1) is already protected.

The tilting adjustment allows the lamp to be tilted up and down about the lateral end (24)
10 of the intermediate connector body (2). The rotational adjustment allows the lamp to be rotated about the open terminal end (21) of the intermediate connector body (2).

CLAIMS

- 1) An adjustable lamp fixture comprising a mounting plate (1), at least an intermediate connector body (2), at least a lamp holder (3) and a motion detection device, is characterised in which
 - 5 at least a first set of standard screw and spring mechanism (4a, 5a, 6a) engages the mounting plate (1) with an open terminal end (21) of the intermediate connector body (2);
 - at least a second set of standard screw and spring mechanism (4b, 5b, 6b) engages one lateral end (23) of the intermediate connector body (2) linking one lamp holder
 - 10 (3);
 - whereas the standard screw and spring mechanism comprises a shoulder screw (4), a tower spring (5) and a compression ring (6),
 - whereby the rotation of the lamp fixture is facilitated about the first set of standard screw and spring mechanism (4a, 5a, 6a), and the tilting of the lamp fixture is
 - 15 facilitated about the second set of standard screw and spring mechanism (4b, 5b, 6b), the facilitation being substantially tool free.
- 2) A tool-free adjustable lamp fixture as in Claim 1 in which the circumference of the open terminal end (21) of the intermediate connector body (2) is appropriately serrated as in a toothed gear (gear C), and the adjacent portion of the mounting plate
- 20 (1) is also appropriately serrated as in a toothed gear (gear D), the two gears (C and D) being meshed or mated with each other, all with the assistance of the first set of standard screw and spring mechanism (4a, 5a, 6a).
- 3) A tool-free adjustable lamp fixture as in Claim 1 in which the circumference of one lateral end (24) of the intermediate connector body (2) is serrated as in a toothed
- 25 gear (gear B), and a side end (31) of the lamp holder (3) is serrated as in a toothed gear (gear A), the two gears (A and B) being meshed or mated with each other, whereas the second set of standard screw and spring mechanism (4b, 5b, 6b) provides sufficient compression force to counter the weight of the lamp holder (3) and the lamp, so that the lamp holder (3) remains in selected position.

- 4) A tool-free adjustable lamp fixture as in Claim 1 in which the compression rings (6a, 6b) in the first and the second sets of standard screw and spring mechanism (4a, 5a, 6a and 4b, 5b, 6b) ensure electrical earth-continuity for various components.
- 5) A tool-free adjustable lamp fixture as in Claim 1 in which an O-ring (7b) is sandwiched between the serrated lateral end (24) of the intermediate connector body (2) and the serrated end (31) of the lamp holder (3).
- 6) A tool-free adjustable lamp fixture as in Claim 1 in which an O-ring (7a) is sandwiched between the mounting plate (1) and the serrated open terminal end (21) of the intermediate connector body (2).
- 10 7) A tool-free adjustable lamp fixture as in Claim 1 in which a gasket (8) is sandwiched between the tower spring (5b) and the compression ring (6b) of the second set of standard screw and spring mechanism (4b, 5b, 6b) installed to the un-serrated lateral end (23) of the intermediate connector body (2).

TOOL-FREE ADJUSTABLE LAMP FIXTURE

ABSTRACT

An adjustable lamp fixture comprises a mounting plate (1), at least an intermediate connector body (2), at least a lamp holder (3) and a motion detection device. There are
5 various mounting methods such as onto a wall or onto a ceiling. At least a first set of standard screw and spring mechanism (4a, 5a, 6a) engages the mounting plate (1) with an open terminal end (21) of the intermediate connector body (2). At least a second set of standard screw and spring mechanism (4b, 5b, 6b) engages one lateral end (23) of the intermediate connector body (2) linking one lamp holder (3). The standard screw and
10 spring mechanism comprises a shoulder screw (4), a tower spring (5) and a compression ring (6) in that order. According to the invention, the rotation adjustment of the lamp fixture is facilitated about the first set of standard screw and spring mechanism (4a, 5a, 6a), and the tilting adjustment of the lamp fixture is facilitated about the second set of standard screw and spring mechanism (4b, 5b, 6b), the facilitation being substantially tool
15 free.

(Figure 2b)

1/4




Figure 1





Figure 2a






Figure 3a




Figure 3b